

## Snow V-plough - Park Ranger 2155



1400 mm



2590-3010 mm



1350 mm  
1987 mm

### Standard equipment:

- Hydraulic angle adjustment** Each side/blade can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blades when needed.
- Vibration damping** A-frame featuring integrated vibration damping, which increases comfort and reduces noise.
- Vulkollan scraper edge** 125 mm high, 25 mm thick and 700 mm wide. The vulcanised rubber scraping edge is good for surfaces that require extra care. The snow V-plough can be mounted with either vulcanised rubber scraper or steel scraper.
- Steel scraper edge** The snow V-plough can be mounted with either steel scraper or vulcanised rubber scraper.
- Safety tilt function** When operating in deep snow there is a risk of hitting obstacles. The safety tilt function of lower part of the V-plough reduces the risk of damages both to the plough and surroundings.
- Floating skids** The 2 skids are height adjustable and ensures that the plough follows ground variations.

### Extra equipment (options):

- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

### Technical specifications

#### Dimensions

|                             |    |             |
|-----------------------------|----|-------------|
| Length                      | mm | 2590-3010   |
| Width (straight)            | mm | 1400        |
| Height with / without cabin | mm | 1987 / 1350 |

#### Storage dimensions

|        |    |      |
|--------|----|------|
| Length | mm | 500  |
| Width  | mm | 1200 |
| Height | mm | 600  |

#### Weight

|                        |    |     |
|------------------------|----|-----|
| Weight (snow V-plough) | kg | 108 |
|------------------------|----|-----|

#### Performance

|                                      |                   |           |
|--------------------------------------|-------------------|-----------|
| Clearing width - straight            | mm                | 1400      |
| Clearing width - inclined            | mm                | 1200-1400 |
| Clearing width - 30°, Y- & V-form    | mm                | 1200      |
| Ground clearance below scraper       | mm                | 140       |
| Ground clearance under support strut | mm                | 125       |
| Operating speed                      | km/h              | 1-16      |
| Handling snow depth up to            | mm                | 500       |
| Turning angle                        |                   | 30°       |
| Theoretical performance              | m <sup>2</sup> /h | 22400     |

#### CE certified according to EU directive

