

Snow plough

- Park Ranger 2155





Standard equipment:

Safety tilt system When operating in deep snow there is a risk of hitting

obstacles. The safety tilt function reduces the risk of damages both to the plough and surroundings.

Rubber scraper edge

100 mm high, 25 mm thick and 1300 mm wide rubber scraper. The scraper edge can be used on two sides giving double usage and extended lifetime.

The rubber scraping edge is ideal for use with melting snow and also scrapes the surface thoroughly without

Floating skids

The 2 skids are height adjustable and ensures that the

blade follows ground variations.

Extra equipment (options):

Anti-corrosion treatment

attachment.

The anti-corrosion treatment will extend the life of the

Technical specifications

Length	mm	2700
Width	mm	1300
Height with / without cabin	mm	1987 / 1350
Storage dimensions		
Length	mm	550
Width	mm	1300
Height	mm	545
Weight		
Weight (snow plough)	kg	64
Performance		
Clearing width - straight	mm	1300
Clearing width - inclined	mm	1130
Ground clearance below scraper	mm	400
Ground clearance under support strut	mm	350
Operating speed	km/h	1-16
Handling snow depth up to	mm	350
Turning angle		30°
Theoretical performance	m²/h	20800
CE certified according to EU directive		



