



# Snow sweeper

## - Park Ranger 2155



1220 mm



3090 mm

1350 mm  
1987 mm

### Standard equipment:

- Trapeze mounting** The trapeze-mounting ensures the snow sweeper remains clear of the wheels of the utility machine at all times, whatever the angle. The snow sweeper automatically turns with the utility machine - always sweeping in front of the wheels of the utility machine.
- Reverse rotation function** Reversing the brush rotation ensures that the operator can sweep material when reversing out of an alley or parking spot, which ensures an excellent result.
- Adjustable speed** The rotation speed can easily be adjusted from the cabin to match the need for sweeping.
- Support stand** A support stand with a wheel is built into the snow sweeper for easy storage.

### Extra equipment (options):

- Extended brush guard** Attaching a brush guard extends the snow sweeper cover, which minimises the snow whirling up on the front wind-screen. Furthermore, the guard makes it easier to control the direction of swept sand and gravel during summer operation. This can be retrofitted on existing snow sweepers as well.
- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

### Technical specifications

#### Dimensions

Length	mm	3090
Width	mm	1220
Height with cabin	mm	1987 / 1350

#### Storage dimensions

Length	mm	900
Width	mm	1220
Height	mm	650

#### Weight

Weight (snow sweeper)	kg	104
-----------------------	----	-----

#### Performance

Clearing width - straight	mm	1220
Clearing width - angled 25°	mm	1140
Ground clearance below brush	mm	420
Brush diameter Ø	mm	550
Operating speed	km/h	1-10
Theoretical sweeping capacity	m <sup>2</sup> /h	12200
Handling snow depth up to	mm	150
Brush speed	rpm	255
Turning angle		25°

#### CE certified according to EU directive

