

Rotary/mulch mower 1200

- City Ranger 2260



Tilting for cleaning	The mower can tilt up and rest on two support wheels making cleaning easy.
Floating function	After lifting the mower it quickly returns to the floating position.
Stepless height adjustment	Cutting height can be infinitely adjusted via handle on the mower.
Piano wheels	Piano wheels which move the cutter in line with the manoeuvring are equipped with heavy slide bearings in their wheel forks for durability.

Extra equipment (options):

Top filter	For extra protection against overheating of the engine it is recommended to equip your City Ranger 2260 with a top filter when mowing the grass.
Mulch mower kit	The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.
Collection mower (kit)	Rebuild the rotary mover to a collection mower. Collecting the grass trimmings ensures the most professional looking result and healthiest lawn. It is recommended to use the dedicated grass collector for this purpose. Please see data sheet on suction sweeper for details.





EGHOLM

1285 mm

2830 mm

Technical specifications

Dimensions		
Length	mm	2830
Width	mm	1285
Height with cabin / roll bar (ROPS)	mm	1939 / 2060
Storage dimensions		
Length	mm	1080
Width	mm	1285
Height	mm	580
Weight		
Weight (rotary mower)	kg	100
Performance		
Ground clearance below mower	mm	100
No. of mower blades	pcs.	2
Cutting speed (tip speed)	m/sec.	73
Cutting width	mm	1210
Adjustable cutting height	mm	30-70
Theoretical mowing area - rotary	m²/h	15730
Theoretical mowing area - mulch	m²/h	12100
Theoretical mowing area - collection	m²/h	12100
Max. recommended operating speed		
Rotary mower *	km/h	13
Mulch mower (shorter grass) *	km/h	10
Collection mower *	km/h	10
Noise emissions		
Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	105
CE certified according to EU directive		
* Depends on grass and height.		





