



Snow plough - City Ranger 2260



1300 mm



2850 mm

1939 mm
2060 mm

Standard equipment:

- Hydraulic angle adjustment** The snow plough angle can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blade when needed.
- Safety tilt system** When operating in deep snow there is a risk of hitting obstacles. The safety tilt function reduces the risk of damages both to the plough and surroundings.
- Rubber scraper edge** 100 mm high, 25 mm thick and 1300 mm wide rubber scraper. The scraper edge can be used on two sides giving double usage and extended lifetime. The rubber scraping edge is ideal for use with melting snow and also scrapes the surface thoroughly without damaging it.
- Floating skids** The 2 skids are height adjustable and ensures that the blade follows ground variations.
- Adjustable weight distribution** For optimum functionality as well as minimum wear of the attachment.

Extra equipment (options):

- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	2850
Width	mm	1300
Height with cabin / roll bar (ROPS)	mm	1939 / 2060

Storage dimensions

Length	mm	515
Width	mm	1300
Height	mm	545

Weight

Weight (snow plough)	kg	66
----------------------	----	----

Performance

Clearing width - straight	mm	1300
Clearing width - inclined	mm	1130
Ground clearance below scraper	mm	420
Operating speed	km/h	1-20
Handling snow depth up to	mm	350
Turning angle		30°
Theoretical performance	m ² /h	26000

CE certified according to EU directive

