

Video



**EGHOLM**

# Salt and sand spreader

- City Ranger 3070



## Standard equipment:

- Start/stop function** The start/stop function ensures that the spreading follows the motion of the vehicle. All spreading stops when the vehicle stops moving.
- Tarpaulin cover** A folded cover keeps the material dry and thereby indirectly improve the spreading accuracy.
- Safety net/grid** A net is placed on the top of the spreader to restrict access into the auger - thereby reducing risk of injuries. The net has an easy lock system, which makes it easy to remove if you need to get access to the auger.
- Holes for forklift** The spreader is constructed with two holes in the bottom which allows for attachment or detachment by a forklift or similar. Thereby the spreader can easily be stored on warehouse racks or similar when not in use.
- Stirrer** The stirrer prevents blocking, crushes lumps and ensures precise and uniform spreading - and thereby even thawing of the ground.
- Ladder** For easy inspection of spreader.
- Speed dependant function** Spreading of material depends on driving speed.

## Extra equipment (options):

- Stand** A stand for attaching/detaching the salt and sand spreader. The stand has wheels, making it easy to move the spreader into storage without heavy lifting. The stand is the same as the one used for the suction sweeper - just use the included adaptor. In case you have a stand already, the adaptor can be bought separately.
- Flash light / beacon** Flash light / beacon on the salt and sand spreader ensures an extra safety parameter.
- Rear working light** The operator can inspect and adjust the spreading disc when working in dark conditions.
- Auger cover for vacuum salt** The cover ensures that tiny material such as vacuum salt, does not just run out of the spreader, which reduces the waste and increase the operation efficiency.
- Tyres 235/60 R 16 (M+S)** The wide tyres are also suitable for winter service. They also have an M+S identifier (snowflake), but generate less ground pressure.
- Tyres 195/70 R 15 (M+S)** When using snow chains, we recommend 15" tyres. Like the 16" wheels, these tyres also have an M+S code and are suitable for winter service use.
- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

## Technical specifications

Dimensions		
Length	mm	4305
Width	mm	1220
Height / with beacon	mm	2000 / 2210
Storage dimensions		
Length with stand	mm	2444
Width with stand	mm	1110
Height with stand	mm	2012
Weights		
Weight (spreader)	kg	295
Payload (spreader) <sup>1)</sup>	kg	950
Spreader		
Volume	l	600
Loading height	mm	1850
Performance		
Spreading width	mm	1500-6000
Operating speed	km/h	1-30
CE certified according to EU directive		

<sup>1)</sup> With no attachment mounted on the A frame.

