



Snow V-plough

- City Ranger 3070



Standard equipment:

Hydraulic angle adjustment	Each side/blade can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blades when needed.
Safety tilt function	When operating in deep snow there is a risk of hitting obstacles. The safety tilt function of lower part of the V-plough reduces the risk of damages both to the snow V-plough and surroundings.
Adjustable weight distribution	For optimum functionality as well as minimum wear of the attachment.
Floating skids	The 2 skids are height adjustable and ensure that the blade follows ground variations.
Vulkollan scraper edge	The vulcanised rubber scraping edge is good for surfaces that require extra care. The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow V-plough can be mounted with either vulcanised rubber scraper or steel scraper.
Steel scraper edge	The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow V-plough can be mounted with either steel scraper or vulcanised rubber scraper.
Indication reflexes	Reflexes marking the edge of the snow V-plough increases the safety for both snow V-plough and surroundings.

Extra equipment (options):

Indication flags	Flags marking the edge of the plough allows for precise positioning and increases the safety for both snow V-plough and surroundings (incl. flex pole).
Side position lights	Side position lights increase the visibility of the snow V-plough.
Support wheels	Designed to operate at higher speeds. Operation is more quiet than with skids and they have less wear reducing costs.
Tyres 235/60 R 16 (M+S)	The wide tyres are also suitable for winter service. They also have an M+S identifier (snowflake), but generate less ground pressure.
Tyres 195/70 R 15 (M+S)	When using snow chains, we recommend 15" tyres. Like the 16" wheels, these tyres also have an M+S code and are suitable for winter service use.
Anti-corrosion treatment	The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	4227
Width (straight)	mm	1600
Height / with beacon	mm	2000 / 2210

Storage dimensions

Length	mm	600
Width	mm	1600
Height	mm	810

Weight

Weight (snow V-plough)	kg	236
------------------------	----	-----

Performance

Clearing width - straight	mm	1600
Clearing width - inclined	mm	1380-1600
Clearing width - 30°, Y- & V-form	mm	1380
Ground clearance below scraper	mm	350
Operating speed	km/h	1-30
Handling snow depth up to	mm	450
Turning angle		30°
Theoretical performance	m ² /h	41400

CE certified according to EU directive

