



Snow blower

- City Ranger 3070



Standard equipment:

Hydraulic adjustment of the chute	The vertical and horizontal direction of the chute is hydraulically adjusted via the joystick from inside the cabin.
Safety feature	In case of clogging, the in-take of the machine is equipped with spring bolts to protect it from over-stress.
Adjustable weight distribution	For optimum functionality as well as minimum wear of the attachment.
Skid	The 2 skids are height adjustable to ensure that the blade adjusts to surface variations.
Blade	The snow blower has a replaceable blade.

Extra equipment (options):

Tyres 235/60 R 16 (M+S)	The wide tyres are also suitable for winter service. They also have an M+S identifier (snowflake), but generate less ground pressure.
Tyres 195/70 R 15 (M+S)	When using snow chains, we recommend 15" tyres. Like the 16" wheels, these tyres also have an M+S code and are suitable for winter service use.
Anti-corrosion treatment	The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions		
Length	mm	4700
Width	mm	1330
Height / with beacon	mm	2300 / 2300
Storage dimensions		
Length	mm	1120
Width	mm	1330
Height	mm	1800
Weight		
Weight (snow blower)	kg	285
Performance		
Clearing width	mm	1300
Feed intake height	mm	700
Ground clearance below snow blower	mm	390
Auger diameter	mm	400
Blower diameter	mm	400
Axle revolutions	rpm	0-1100
Operating speed	km/h	1-7
Noise emissions		
Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	106
CE certified according to EU directive		

